

TORO

Power Clear™ Single Stage Specifications

MODEL**221R/E**

Model 38581/38582

221QR/QE

Model 38583/38584

421QR/QE

Model 38585/38586

**Clearing Width
Throw Distance†**21"
up to 30'21"
up to 30'21"
up to 35'**Engine**Toro R*Tek®
141cc 2-cycleToro R*Tek
141cc 2-cycleTecumseh® 5.5hp*
L-Head 4-cycle**Starter**

Recoil / Electric Start

Recoil / Electric Start

Recoil / Electric Start

Fuel Capacity

1.0 Quarts

1.0 Quarts

1.0 Quarts

**Chute Direction
Control**

Chute Mounted Handle



Quick Shoot™

Quick Shoot

**Chute Deflector
Control**

Zip Deflector

Zip Deflector

Zip Deflector

Chute MaterialCommercial Grade
PolyethyleneCommercial Grade
PolyethyleneCommercial Grade
Polyethylene**Auger System**

Power Curve®

Power Curve

Power Curve

Rotor TypePolyester-Ply
Rubber PaddlesPolyester-Ply
Rubber PaddlesPolyester-Ply
Rubber Paddles**Drive System**Power Propel™
Self-PropelPower Propel
Self-PropelPower Propel
Self-Propel**Weight**

71 lbs. / 74 lbs.

73 lbs. / 76 lbs.

79 lbs. / 81 lbs.

Starting Guarantee5 Year
Guaranteed to Start5 Year
Guaranteed to Start5 Year
Guaranteed to Start**Warranty****

2 Year FULL

2 Year FULL

2 Year FULL

Features

**Quick Shoot™
Control System**Quickly and easily
change direction by
squeezing the trigger
and sliding the handle
mounted grip.**Zip Deflector**Positive-locking ratchet
deflector allows you to
throw snow low or let
it fly.**Power Curve®
Rotor**Clean right down to
the pavement with
the rubber paddles of
the Power Curve rotor.**Powerful Engine**Your choice of the
easy-starting Toro R*Tek
2-cycle or powerful
Tecumseh 4-cycle
engine.

= Enhanced or Step-up feature

© 2007 The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. * The gross horsepower of this engine was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission, and operating requirements, the actual engine horsepower on this class of snowthrower will be significantly lower. **See retailer for warranty details. † Throw distance will vary with conditions. 490-7647